



**TITLE: TENDER FOR SUPPLY MATERIAL**

**TENDER REFERENCE NUMBER: REMCO/PM/08/2025-2026**

**PROCURING ENTITY: RWANDA ENGINEERING AND  
MANUFACTURING CORPORATION (REMCO)**

**PROCUREMENT METHOD: OPEN COMPETITIVE BIDDING**

**DATE OF ISSUE: 28<sup>th</sup> April 2026**

**DEADLINE OF SUBMISSION: 07<sup>th</sup> May 2026**

*NE*

## SECTION 1. INTRODUCTION AND BACK GROUND

### SECTION 2. SCOPE OF SERVICE

The successful bidder shall be required to provide these material as per the required specification and requirements mentioned in this document below in the best quality and they must be able to serve the purpose for which they are intended to.

The above services shall be offered at the successful bidder's premises and shall be rendered successful upon thorough and clear inspection by the appointed member of REMCO staff.

### SECTION 3. TENDER PRESENTATION AND REQUIREMENTS

All tenders must include and present the following phases and they will be evaluated in the same fashion.

#### 3.1. ADMISTRATIVE ELIGIBILITY

All bidders shall provide the following documents as the first criteria to be followed for the first stage of evaluation.

- a. A valid business registration certificate
- b. A valid company profile

#### 3.2. TECHNICAL QUALIFICATION AND INSTRUCTIONS

All bidders shall present the following as the second criteria to be followed in the second stage of evaluation.

- a. A list of specifications that must correspond to the following specifications. Lower specification will not be tolerated or accepted.

<b>LOT 3: Civil Works, Water Storage &amp; Structures</b>		
1	Dam sheets 480m <sup>2</sup> , The Tensile strength: $\geq 300\text{N/MM}^2$ , The Tear strength: $\geq 18\text{N/MM}^2$ ; The Elongation at break: $\geq 394\%$ ; The Shrinkage: $\geq 0.04\%$ ; The bursting strength: $\geq 30 \text{ DAN/CM}^2$ , The UV treatment: 100%; The Recyclable: 100%; The Thickness: 0.9-1.0MM (One millimeter), made of HDPE Material	1
2	Dam sheets 250m <sup>2</sup> , The Tensile strength: $\geq 300\text{N/MM}^2$ , The Tear strength: $\geq 18\text{N/MM}^2$ ; The Elongation at break: $\geq 394\%$ ; The Shrinkage: $\geq 0.04\%$ ; The bursting strength: $\geq 30 \text{ DAN/CM}^2$ , The UV treatment: 100%; The Recyclable: 100%; The Thickness: 0.9-1.0MM (One millimeter), made of HDPE Material	1

3	Dam sheets 120m <sup>2</sup> , The Tensile strength: $\geq 300\text{N/MM}^2$ , The Tear strength: $\geq 18\text{N/MM}^2$ ; The Elongation at break: $\geq 394\%$ ; The Shrinkage: $\geq 0.04\%$ ; The bursting strength: $\geq 30\text{ DAN/CM}^2$ , The UV treatment: 100%; The Recyclable: 100%; The Thickness: 0.9-1.0MM (One millimeter), made of HDPE Material	1
4	Excavation and refilling per cubic meter in normal soil	1
5	Excavation and refilling per cubic meter in water	
6	Excavation and refilling per cubic meter in rock soil	
7	Wire mesh (Senyenge) from 20×20 mesh to 30×30 mesh of 1.8 meters height per linear meter	1
8	480 m <sup>3</sup> Dam sheets Fencing, Galvanized Wire mesh from 20×20 mesh to 30×30 mesh of 1.8 meters height, fixed on metallic tube of 60/40 as main support and 40*40 as with 1.2 mm as second support casted in concrete to avoid collusion and door made in tubes	1
9	250 m <sup>3</sup> Dam sheets Fencing, Galvanized Wire mesh from 20×20 mesh to 30×30 mesh of 1.8 meters height fixed on metallic tube of 60/40 as main support and 40*40 as with 1.2 mm as second support casted in concrete to avoid collusion and door made in tubes	1
10	120 m <sup>3</sup> Dam sheets Fencing, Galvanized Wire mesh from 20×20 mesh to 30×30 mesh of 1.8 meters height	1
11	Construction and lining of stone masonry per cubic meter	1
12	Construction of Concrete masonry per cubic meter	1
13	Construction of Reinforced Concrete masonry per cubic meter	1
14	Construction of one cubic meter of non-reinforce concrete, non-reinforced concrete of class B25	1
15	Construction of one cubic meter of reinforce concrete, Reinforced concrete as requested by the site of class B25	1
16	Construction of burnt bricks bedded and jointed in cements and sand mortar per cubic meter	1
17	Roof cover, Auto portant GB 30 per m <sup>2</sup>	1
18	Metallic tube 80/80, Thickness 1.5	1
19	Metallic tube 80/60, Thickness (1.5)	1
20	Metallic tube 80/40, Thickness (1.5)	1
21	Metallic tube 60/40, Thickness (1.5)	1
22	Metallic tube 40/40, Thickness (1.5)	1
23	1,000 L Tank, Plastic Polyethylene	1
24	2000 L Tank, Plastic Polyethylene	1
25	3000 L Tank, Plastic Polyethylene	1

26	2,500L Tank, Plastic Polyethylene	1
27	5000L Tank, Plastic Polyethylene	1
28	10000L Tank, Plastic Polyethylene	1
29	WATER BLADDER, 10000 Lts, Base cloth: PES/PES; Mass per unit area/Total weight (approx.): 1257g/m <sup>3</sup> ; coating color: Dull sand; Breaking strength; 4045N/5cm width; warp-way, (N) Breaking strength; 3940N/ 5cm width; weft-way, (N); Tear strength: warp-way, 609N. Tear strength: weft-way, 720N; Adhesion 100N/5cm; thickness, (1.02mm). Temperature resistance -30° to +70°C; color: army green camouflage; special properties: special quality for contact potable water.	1
30	WATER BLADDER, 20000 Lts, Base cloth: PES/PES; Mass per unit area/Total weight (approx.): 1257g/m <sup>3</sup> ; coating color: Dull sand; Breaking strength; 4045N/5cm width; warp-way, (N) Breaking strength; 3940N/ 5cm width; weft-way, (N); Tear strength: warp-way, 609N. Tear strength: weft-way, 720N; Adhesion 100N/5cm; thickness, (1.02mm). Temperature resistance -30° to +70°C; color: army green camouflage; special properties: special quality for contact potable water.	1
31	First 20 m drilling (210mm diameter and 200mm length, with flashing water as compressor or airlift) (Casing pipe of 140mm and at least 50 cm length of holes of 2mm, gravel also should be used to facilitate infiltration)	1
32	1 Meter drilled after 50 m depth (210mm diameter and 200mm length, with flashing water as compressor or airlift) (Casing pipe of 140mm and at least 50 cm length of holes of 2mm, gravel also should be used to facilitate infiltration)	1
33	Complete 20 m drilling with submersible pump kit (210mm diameter and 200mm length, with flashing water as compressor or airlift) (Casing pipe of 140mm and at least 50 cm length of holes of 2mm, gravel also should be used to facilitate infiltration)	1
34	Complete 50 m drilling with submersible pump kit (210mm diameter and 200mm length, with flashing water as compressor or airlift) (Casing pipe of 140mm and at least 50 cm length of holes of 2mm, gravel also should be used to facilitate infiltration)	1



35	More than 50 m drilling with submersible pump kit (210mm diameter and 200mm length, with flashing water as compressor or airlift) (Casing pipe of 140mm and at least 50 cm length of holes of 2mm, gravel also should be used to facilitate infiltration)	1
36	Metallic Stand Height 1.5 Mtrs (500 LTR)	1
37	Metallic Stand Height 1.5 Mtrs (1000 LTR)	1
38	Concrete/Stone Masonry Structure for Tank (L-, H-, W-) 5000 LTR	1
39	Concrete/Stone Masonry Structure for Tank (L-, H-, W-) 10000 LTR	1

### 3.3. FINANCIAL PROPOSAL

All bidders shall present their financial offers and these shall be competitive and must spell value for money. This shall be third criteria to be followed in the third stage of evaluation.

The financial evaluation will be conducted according to prices offered for every item as they are presented on the table attached above.

- Every bidder shall provide a well signed and stamped financial offer.
- Every offer shall be presented in the Local currency which is Rwanda francs (RWF)

### SECTION 4. SUBMISSION OF OFFERS

Offers must be submitted not later than 07<sup>th</sup> May 2026 at 23:59 Pm Local time, late offers will be rejected and will not be opened or considered.

- Offers must be submitted by email through [procurement@remco.rw](mailto:procurement@remco.rw). Any queries must be addressed to the CEO of REMCO and sent to the same email with [info@remco.rw](mailto:info@remco.rw) in copy.
- The language to be used as the medium of communication in all the offers shall be in English.
- This tender shall only be valid for Seven (7) working days.

### SECTION 5. OTHER TERMS AND CONDITIONS

- REMCO reserves the right to visit any bidder's location/premises during tender evaluation.
- All bids shall be opened and evaluated in the absentia of all bidders.
- REMCO reserves the right to reject any offer where, in its opinion, a conflict of interest exists or may arise such as influence of any kind, professional or financial relationships with employees
- All payments shall be made by cheque or bank transfer, in accordance with the agreed contractual terms and conditions We are looking forward to receiving your great offers.

*NE*

**Sincerely**



**Eric NYAMUHENDA**  
Acting Chief Executive Officer  
REMCO Ltd